


JT440-450SGh(1500) Monocrystalline Solar Module

144 Cells / Mono PERC / 1500V DC / 20.6% Maximum Efficiency



KEY FEATURES



Higher module conversion efficiency

Maximize limited space with high efficiency mono PERC cells
Half-cell design, lower Rs loss, lower hot spot temperature



Highly reliable due to stringent quality control

100% EL double inspection
In-house testing goes well beyond certification requirements



Excellent low light performance

Excellent low light performance on cloudy days
mornings and evenings



Certified to withstand the most challenging environment

2400 Pa wind load • 5400 Pa snow load • 25 mm hail stones at 82 km/h



High system voltage compatible

Maximum 1500V DC system voltage saves total system cost



IP67 junction box

High waterproof level for long term weather endurance

QUALIFICATIONS & CERTIFICATES

- IEC 61215, IEC 61730
- ISO 9001: Quality Management System
- ISO 14001: Environment Management System
- OHSAS 18001: Occupational Health and Safety

JETION SOLAR

As a member of CNBM - a Fortune 500 company, Jetion Solar provides various product solutions, global EPC service and financing. Its standard and high-efficiency product offerings are among the most powerful and cost-effective in the industry. Till now, Jetion Solar has cumulatively more than 10 GW module shipment and 1 GW global EPC track records.

WARRANTY



Product
Warranty




Product
Warranty



Performance
Warranty

* Applies to rooftop market
in Australia only.



Jetion Solar (China) Co., Ltd.

Add: 1011 Zhencheng Road, Jiangyin, Jiangsu Province, P.R. China 214443



Tel: +86 (510) 8668 7300

E-mail: marketing@jetion.com.cn

Web: www.jetion.com.cn



IV CURVES



ELECTRICAL DATA *STC

	JT440SGh (1500)	JT445SGh (1500)	JT450SGh (1500)
Maximum Power Pmax (W)(tolerance±3% selection limits-0/+5W)	440	445	450
Maximum Power Voltage Vmp (V)	41.0	41.2	41.4
Maximum Power Current Imp (A)	10.74	10.81	10.87
Open Circuit Voltage Voc (V)(tolerance±2%)	49.6	49.8	50.0
Short Circuit Current Isc (A)(tolerance±3%)	11.30	11.37	11.44
Module Efficiency (%)	20.1%	20.4%	20.6%

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5

TEMPERATURE RATINGS

Temperature Coefficient of Isc (αIsc)	+0.05%/°C
Temperature Coefficient of Voc (βVoc)	-0.30%/°C
Temperature Coefficient of Pmax (γPmp)	-0.35%/°C
Normal Module Operating Temperature (NMOT)	41°C±3°C


OPERATING PARAMETERS

Maximum System Voltage	1500V/DC(IEC)
Operating Temperature	-40°C~+85°C
Maximum Series Fuse	20A
Maximum Test Load,Push/Pull	5400Pa/2400Pa
Conductivity at Ground	≤ 0.1Ω
Safety Class	II
Resistance	≥ 100MΩ
Voc and Isc Tolerance	±3%

MECHANICAL DATA

Solar Cell Type	Mono 83×166 mm(6 inches)
Number of Cells	144 [2 x (12 x 6)]
Module Dimensions	2102×1040×35 mm(82.8×40.9×1.4 inches)
Weight	24.5 kg(54 lb)
Front Cover	3.2 mm (0.13 inches), high transmission, AR coated tempered glass
Back Cover	White composite film
Frame	Silver, anodized aluminium alloy
J-Box	≥IP67
Cable	4.0 mm² solar cable, 150/300 mm(5.9/11.8 inches)
Number of diodes	3
Connector	PV-ZH202B, 05-8, PV-JM608

DIMENSION



Remarks

*Installation instruction must be followed. See the installation manual or contact our technical service department for further information on approved installation.
 *The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to ongoing innovation, R&D enhancement, Jietion Solar (China) Co., Ltd. reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein. Jietion Solar_REV_2021_01_EN Made in China or Made in Thailand

